

BENCHTOP WATER ACTIVITY

- **Accurate**— $\pm 0.003 a_w$
- **Verifiable**—with independent salt standards.
- **Repeatable**—different users, different locations, same result.
- **Portable**—the meter weighs just 7 pounds.
- **Easy to use**—precise measurements with minimal training.
- **Secure**—offers administrative control over calibration and sample data.
- **Proven**—used by 80 of the top 100 food companies.

Fast—water activity readings in 5 minutes or less.

ENSURE THE SAFETY AND QUALITY OF YOUR PRODUCTS

Use AquaLab to get lab-quality water activity measurements at the line, receiving dock, processing plant, storage facility—anywhere you need to verify the safety and quality of your products and ingredients.

Speed and Accuracy

Measure water activity in 5 minutes or less (average read time: 2.5 minutes) with $\pm 0.003 a_w$ accuracy. AquaLab instruments are the fastest, most precise water activity meters available.

Use (Almost) Anywhere

Water activity is temperature dependent. Internal temperature control lets you set a measuring temperature between 15°- 50°C and use the instrument anywhere—even outside a climate-controlled facility.

How it Works

Put a 7.5 ml product sample in a disposable cup, seal the sample chamber lid over the sample, and wait for vapor equilibrium.

An infrared beam focused on a tiny mirror determines the precise dewpoint temperature of the sample. That dewpoint temperature is then translated into water activity.

Easy to Clean

The sample chamber lid flips up so contaminated sensors are quick to spot and easy to clean.

Secure Data

The 4TE stores time, date, and user information with every measurement and calibration, and can store up to 10,000 secure data points.

Administrative functions can be set to control access to

data. Designate up to 5 unique users and passwords. Use the RS-232 serial data port to download or print data for statistical analysis and to maintain compliance records and archives.

Easy to Use

AquaLab Series 4TE makes water activity measurements quick, accurate, and simple. Using AquaLab, anyone, from a researcher in the lab to an operator at the line, can measure water activity in 5 minutes or less to 0.003 a_w specifications. That means tighter control points, better quality, and a leaner operation.

Learn More

Visit aqualab.com to see how water activity can keep your products safe and your process lean. ■



**AQUA
LAB**
BY DECAGON

2365 NE Hopkins Court
Pullman, Washington 99163

1-800-755-2751

Int'l: 509-332-2756

Specifications

AquaLab Series 4TE Water Activity Meter



Free Loaner Service

Free Technical Support

Free Application Support
over the life of the instrument

Sensor Types

- Chilled-mirror dewpoint.
- Infrared temperature.

Accuracy

±0.003 a_w

Repeatability

±0.001 a_w

Resolution

±0.0001 a_w

Range

0.030 to 1.000 a_w

Sample Dish Capacity

7 ml recommended (15 ml full).

Measurement Time

Less than 5 minutes.

Display

128x64 pixel lcd display
with backlighting.

Temperature Control

15 to 50°C (±0.2°C)

Test Result Memory

10,000 readings (each reading includes water activity, moisture content, temperature, time, date, operator, and sensor used)

Program Identification

Alphanumeric; Programmable to display product name, lot, or product ID number.

Operating Environment

4 to 50°C (39.2 to 122°F)
0 to 90% Relative Humidity
(non-condensing.)

Universal Power

110 V to 220 V AC, 50/60 Hz
Less than 0.4 amps.

Data Interface

RS232A compatible,
8-data bit ASCII code,
9600 baud, no parity, 1 stop bit,
cable included.

Case Dimensions

26.7 x 27.8 x 12.7 cm
(11 x 7.1 x 5.1 in)

Case Material

Machined aluminum frame;
injection molded plastic cover.

Weight

3.18 kg (6.9 lb)

Warranty

Three years, factory parts & labor.

Certifications

CE; AOAC Approved Method for
Measurement of Water Activity,
Part 11 Compliance

©2011 DECAGON
PRINTED IN USA

**AQUA
LAB**
BY DECAGON

2365 NE Hopkins Court
1-800-755-2751
Int'l: 509-332-2756
Pullman, WA, USA 99163